


NO.	MASSE / DIMENSION
D1	35.4
D2	23.9
D	15.9
E	0.23
G	35
K	3.89
L1	47
L2	15.9

NO.	BESCHREIBUNG / DESCRIPTION
2	ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET
4	DICKTKÖRPER / GROMMET
5	ENDRING / ENDRING
7	KONTAKT BUCHSE / CONTACT SOCKET
8	GEHÄUSE / RECEPTACLE
9	ENDGEHÄUSE / ENDBELL
12	ÜBERWURFMUTTER / COUPLING NUT
14	WELLFEDER / WASHER
15	KABELTÜLLE / BUSHING
16	KABELKLEMME / CABLE CLAMP
20	ZYLINDER-SCHRAUBE / CYLINDER HEAD SCREW



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Notiz: Durch ein automatisches Benennungssystem können Nummerierungen entstehen, die nicht fortlaufend sind.

Material Specification:	
Shell Material:	ALUMINIUM ALLOY
Shell Plating:	OLIVE DRAB CHROMATE OVER CADMIUM PLATING
Insulator Material:	POLYCHLOROPRENE
Contact Material:	COPPER ALLOY, GOLD PLATED
Contact Plating:	COPPER ALLOY, GOLD PLATED

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for
 CUSTOMER



description MS3116F1832S
 STRAIGHT PLUG
 GROMMET SEAL WITH STRAIN RELIEF
 SOLDER CUP / SOCKET / Layout: 1832

© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon



page 1/1
 revision 42.7